

## Stripping and crimping machines

### Stripping and crimping machines

- Efficient and time-saving processing of linked wire end ferrules with plastic collar on reel.
- Easily adjustable on conductors diameter
- Stripping- and crimping in one operation
- Changeover tool for Crimpfix 2.5 MT 0.34
- Flexible and fast in use, all-electric drive

### Crimpfix 2.5 M



The Crimpfix 2.5 M is an electrically driven stripping and crimping machine for processing reels of linked wire end ferrules with plastic collar. The cam-operated drive mechanism works without pneumatic support. The crimping machine is compact and easy to use, and hence a convenient addition to any workplace. The simple setting of the crimping drum to the respective cross-section range makes time-consuming tool changes only necessary if a cross-section of 0.34 mm<sup>2</sup> is wanted.

- Stripping and crimping in the range 0.5 - 2.5 mm<sup>2</sup> / 0.34 mm<sup>2</sup>

#### Technical data

Specification		Crimpfix 2.5 M
Stripping range	mm <sup>2</sup>	0.34 / 0,5 – 2,5
Crimping length / Crimping range	mm	6 / 8
Cycle time		2,5 s
Cross-section range	mm <sup>2</sup>	0.34 / 0,5 – 2,5
Connected electrical loads		230V / 50Hz / 100VA
Tool data		
Dimensions D x W x H	mm	310 / 292 / 260
Weight	kg	15

#### Ordering data

Version	Typ	Qty.	Order No.
	Crimpfix 2.5 M	1	9205410000

#### Accessories

Version	Typ	Qty.	Order No.
	Crimpfix 2.5 MT 0.34	1	9205420000